

# movexx

smart electric tugs



## Technical datasheet

# TT1500-S

M020



» move your work easier

# TECHNICAL DATA TT1500-S M020

According to VDI 2198

<b>Characteristics</b>	1.1	Manufacturer		Movexx International B.V.	
	1.2	Model designation		TT1500-S	
	1.3	Power unit		Electric w. LiFePo4 battery	
	1.4	Operation type		Pedestrian	
	1.5*	Rated capacity/Load capacity	Q [t]	1.5	
	1.7**	Rated drawbar pull	F [N]	490	
<b>Wt</b>	1.9	Wheelbase	y [mm]	560	
	2.1	Weight, incl battery	kg	190	
<b>Wheels / tyres</b>	2.2	Axle load without load	front/rear	kg	90/100
	3.1	Tyres		Solid rubber	
	3.2	Tyre size	front	mm	250 x 85
	3.3	Tyre size,	rear	mm	125
	3.4	Auxiliary wheel size		mm	-
	3.5	Wheels, number front/rear (x = drive)			1/x2
<b>Dimensions</b>	3.6	Tread width	front/rear	$b_{10}/b_{11}$ [mm]	-/403
	4.8	Stand height	min./max.	$h_7$ [mm]	-
	4.9	Tiller height	min./max.	$h_{14}$ [mm]	910-1027-1110
	4.12	Tow coupling height		$h_{10}$ [mm]	85 - 275
	4.19	Total length		$l_1$ [mm]	1303
	4.21	Total width		$b_1$ [mm]	487
	4.32	Ground clearance, center of wheel base		$m_2$ [mm]	50
4.35	Turning radius		$W_a$ [mm]	1106	
<b>Performance</b>	5.1	Travel speed forwards	with/without load	km/h	4/4
	5.1.1	Travel speed backwards	with/without load	km/h	4/4
	5.5**	Max. drawbar pull (S2 = 60 Min)	with/without load	N	460
	5.6**	Max. drawbar pull (S2 = 5 Min)	with/without load	N	980
	5.8*	Maximum slope (5 min)	with/without load	%	0/15
	5.9	Acceleration	with/without load	s	8/6
5.10	Service brake			Electromagnetic	
<b>Drive</b>	6.1	Drive motor output (S2 = 60 Min)		kW	0,6
	6.4	Battery voltage, nominal capacity		[V/Ah]	24/20
	6.5	Battery weight +/- 5%		kg	8,4
<b>Other</b>	8.1	Drive control			DC
	10.7	Noise level		dB(A)	65

\* The maximum payload is affected by the type of slope, operating time and floor type.

\*\* The maximum drawbar load on the hook [N] is determined by the engine power of the machine but is affected by the type of wheels of the machine and of the towed trolley/load, the type of surface and the driveable weight of the machine.

