

moveXX

smart electric tugs



Technical datasheet

TT2000-M-Inox

M020



» move your work easier

TECHNICAL DATA TT2000-M-Inox M020

According to VDI 2198

Characteristics	1.1	Manufacturer		Movexx International B.V.	
	1.2	Model designation		TT2000-M-Inox	
	1.3	Power unit		Electric w. LiFePo4 battery	
	1.4	Operation type		Pedestrian	
	1.5*	Rated capacity	Q [t]	2	
	1.7**	Rated drawbar pull	F [N]	800	
	1.8	Load distance, center of drive axle to	x [mm]	710-460	
	1.9	Wheelbase	y [mm]	950-700	
	Weight	2.1	Weight, incl battery	kg	140
2.2***		Axle load with load	front/rear	kg	251/69
2.3***		Axle load without load	front/rear	kg	116/24
Wheels / tyres	3.1	Tyres R = rubber, PU = polyurethane		PU/R	
	3.2	Tyre size	front	mm	200
	3.3	Tyre size,	rear	mm	125
	3.4	Auxiliary wheel size		mm	-
	3.5	Wheels, number front/rear (x = drive)			1x/2
	3.6	Tread width	front/rear	b_{10}/b_{11} [mm]	60/50
Dimensions	4.9	Tiller height	min./max.	h_{14} [mm]	650/1080
	4.19	Total length		l_1 [mm]	923-1173
	4.20	Length to load face		l_2 [mm]	-
	4.21	Total width		b_1 [mm]	460-656
	4.32	Ground clearance, center of wheel base		m_2 [mm]	32,5
4.35	Turning radius		W_a [mm]	915-1165	
Performance	5.1	Travel speed forwards	with/without load	km/h	2/4,5
	5.1.1	Travel speed backwards	with/without load	km/h	2/4,5
	5.5**	Max. drawbar pull (S2 = 60 Min)	with/without load	N	400
	5.6**	Max. drawbar pull (S2 = 5 Min)	with/without load	N	800
	5.8*	Maximum slope (5 min)	with/without load	%	0/10
	5.9	Acceleration	with/without load	s	10/8
	5.10	Service brake			Electromagnetic
Drive	6.1	Drive motor output (S2 = 60 Min)		kW	0,7
	6.4	Battery voltage, nominal capacity		[V/Ah]	24/36
	6.5	Battery weight +/- 5%		kg	12
Other	8.1	Drive control			DC
	10.7	Noise level		dB(A)	65

* The maximum payload is affected by the type of slope, operating time and floor type.

** The maximum drawbar load on the hook [N] is determined by the engine power of the machine but is affected by the type of wheels of the machine and of the towed trolley/load, the type of surface and the driveable weight of the machine.

*** Values vary with different wheel base lengths (1.9[y]).

